



ROLLER



PANEL



ROMAN

Technical Data

Composition	100% Polyester
Width	3,000mm
Weight	Blockout 430gsm +/-5% Light filtering 210gsm +/-5%
Thickness	Blockout 0.60mm +/-5% Light filtering 0.40mm +/-5%
Opacity/Openness	Blockout tested to AS-2663-1999
Light Fastness	≥ 5 (Blue wool scale)
Coating	Blockout coated with acrylic foam Light filtering stiffened with acrylic
Flame Retardant	Product is designed and manufactured to comply with Building Code of Australia requirements for class 2 to 9 buildings
Cleaning	Surface dust can be removed with vacuum or a soft cloth



5 YEAR WARRANTY



BLOCKOUT



LIGHT FILTERING



ECO FRIENDLY



PVC FREE



STANDARD 100



Solar Properties

	Ts	Rs	As	Tv	Rv	High Performance Glass Reference Glazing D [g window 0.32] [U window 1.1] g-total
Blockout	0	83	17	0	0	0.23
Plaster LF	35	52	13	35	54	0.35
Marble LF	32	53	15	32	53	0.34
Limestone LF	33	48	19	32	48	0.35
Ceramic LF	32	36	32	30	29	0.39
Truffle LF	26	41	33	22	34	0.35
Fossil LF	23	33	44	16	22	0.36
Suede LF	31	43	26	28	39	0.36
Mineral LF	34	48	18	33	48	0.36
Slate LF	26	39	35	21	31	0.35
Baltic LF	25	32	43	17	20	0.37
Lava LF	21	28	51	10	12	0.36

Ts Solar Transmittance

As Solar Absorbance

Rv Visual Light Reflectance

Rs Solar Reflection

Tv Visual Light Transmission

G-Total % Solar Radiation through Blind and Window

Melbourne Head Office

Building 1, Level 2, 630 Mitcham Road
Mitcham VIC 3132 Australia

P +61 3 9729 9970
E sales@texstyle.com.au

Learn more at
texstyle.com.au/sanctuary

