Barbados

ROLLER PANEL ROMAN

Technical Data

Composition	100% Polyester
Width	2,800mm
Weight	378gsm +/-5%
Thickness	0.53mm +/-5%
Opacity/Openness	Blockout tested to AS-2663-1999
Light Fastness	≥ 5 (Blue Wool Scale)
Coating	Blockout coating with Acrylic Foam
Flame Retardant	Product is designed and manufactured to comply with Building Code of Australia requirements for class 2 to 9 buildings
Cleaning	Surface dust can be removed with vacuum or a soft cloth

Solar Properties

	European standard tested to DIN EN 410: 2011						**Tested to EN 14501**	
	Ts	**Rs**	**As**	**Tv/ Vlt**	**Tuv**	**O-F**	**Single Glass Reference Glazing A [g window 0.85] [U window 5.7] g-total**	**High Performance Glass Reference Glazing D [g window 0.32] [U window 1.1] g-total**
Barbados Blockout	0	73	27	0	0	0	0.29	0.24

Ts Solar Transmittance **As** Solar Absorbance **Tv** Visual Light Transmission **G-Value** % Solar Radiation through Fabric

Rs Solar Reflection **Tuv** Ultraviolet Transmittance **O-F** Openness Factor **G-Total** % Solar Radiation through Blind and Window

texstyle.com.au
Phone. 03 9729 9970

FIVE YEAR WARRANTY 5

TEXSTYLE