

# Sanctuary



## Technical Data

<b>Composition</b>	100% Polyester
<b>Width</b>	3,000mm
<b>Weight</b>	430gsm +/-5%
<b>Thickness</b>	0.60mm +/-5%
<b>Opacity/Openness</b>	Blockout, tested to AS-2663-1999
<b>Light Fastness</b>	≥ 5 (blue wool scale)
<b>Coating</b>	Blockout coated with acrylic foam
<b>Flame Retardant</b>	Product is designed and manufactured to comply with Building Code of Australia requirements for class 2 to 9 buildings.
<b>Cleaning</b>	Surface dust can be removed with vacuum or a soft cloth

## Solar Properties

	European standard tested to DIN EN 410: 2011						Tested to EN 14501	
	Ts	Rs	As	Tv/ Vlt	Tuv	O-F	Single Glass Reference Glazing A [g window 0.85] [U window 5.7] g-total	High Performance Glass Reference Glazing D [g window 0.32] [U window 1.1] g-total
Sanctuary Blockout	0	75	25	0	0	0	0.27	0.24

**Ts** Solar Transmittance

**As** Solar Absorbance

**Tv** Visual Light Transmission

**G-Value** % Solar Radiation through Fabric

**Rs** Solar Reflection

**Tuv** Ultraviolet Transmittance

**O-F** Openness Factor

**G-Total** % Solar Radiation through Blind and Window

[textstyle.com.au](http://textstyle.com.au)

Phone. 03 9729 9970



**TEXTSTYLE**